


VECTOR CONNECTOR NEGATIVE DRAFT

NOTES:

- 1.) CENTER WELD AND FIELD PLATE WITHIN FACEPLATE OF VECTOR CONNECTOR. DO NOT WELD AT CORNERS.
- 2.) DO NOT OVER WELD; 3" MAXIMUM WELD LENGTH.
- 3.) FIELD PLATE TO BE HORIZONTAL.
- 4.) TOP EDGE OF VECTOR CONNECTOR MUST BE CLEAN.
- 5.) LOCATE LONGITUDINAL AND TRANSVERSE WIRE OF WWF MESH SO NOT TO INTERFERE WITH VECTOR CONNECTOR LEG ENDS; ORDER WWF MESH WITH PROPER CLEARANCE.
- 6.) DETAIL OF JOINT BEYOND NOT SHOWN; SEE JVI-SK3
- 7.) FOR A304 STAINLESS STEEL VECTOR CONNECTORS, USE A304 STAINLESS STEEL ERECTION PLATES AND USE WELDING ELECTRODE E308.
- 8.) FOR "J" COATED VECTOR CONNECTORS (A36), USE A36 GRADE ERECTION PLATES AND USE WELDING ELECTRODE E70XX.

CONNECTION AT EACH
DOUBLE TEE JOINT AT
4'-0" ON CENTER



JOINT DETAIL BEYOND CONNECTION

TYP. D-TEE TO D-TEE FLANGE CONNECTION

SCALE: 3/4" = 1'-0"

STRESS-CON **INDUSTRIES, INC.**

MAIN OFFICE:
50500 DESIGN LANE TEL: (586) 731-1628
SHELBY TOWNSHIP, MI 48315 FAX: (586) 731-7007
WWW.STRESSCONINDUSTRIES.COM

PROJECT NO.

DRAWN

SCALE

CHECKED

DATE

ISSUED FOR

REF.

PROJECT

SHEET NO.